


MONUMENT RECORD
Corner ID: **Rich_M11**
Section Corner
Sections 15 & 16- T09N-R02W, 2nd P.M.
Richland Township, Monroe County, Indiana



EXISTING SURVEY HISTORY

Include as much detail and history of the corner as known at the time of perpetuation.

ORIGINAL GOVERNMENT SURVEY:

Year Surveyed: **1815** By: **William Harris**
Where filed or recorded: **Original Notes Page 337**
Original monument: **Post**
Bearing Trees or Reference Monuments:

Species	Dia.	Bearing	Distance
Sugar	12"	S 86° E	4 Links
	27"	S 59° W	23 Links

Notes:

SUBSEQUENT CORNER RESTORATION:

Date Surveyed: **5/25/2000** By: **Kevin P. Enright**
Where filed or recorded: **M.C.S.O. Records**
Original monument: **PK Nail**
Bearing Trees or Reference Monuments:

I.D.	Dia.	Bearing	Distance
Rebar w/ Cap	1/2"	S 84° E	25.00'
"X" on F.H. Bolt		S 17° E	76.64'
Mag in P.P.		S 18° W	46.50'

Notes:

SURVEY EVIDENCE FOUND: Include evidence found and weighed, search area or areas, search procedure, etc.
Date of Search: **11/8/21** By: **J.R. & E.D.** Monument Found: **PK Nail** BTs or Reference Objects Found: **1/2" Dia. Rebar with "Mundy" Cap, "X" in Fire Hydrant Bolt, Mag 9" A.G. in East side of Power Pole** Notes:

OTHER SURVEY HISTORY: Include details such as surveyor name, date, recording info, monument description, etc.

PERPETUATION RECORD

MONUMENT: Describe monument set or found (Include material type, scribing, distance above/below grade, dimensions.)
A mag nail found in Thomas Road. To better preserve the location of this corner, the mag nail was replaced with a mag spike with a washer stamped "Deckard" set 2 inches below grade.

OTHER EVIDENCE: Describe corner location relative to nearby features and how to reach the corner location – note fences, roads, timber cutting lines, mow lines, clearings, plantings, streams, topo changes, etc.
Corner in Thomas Road (Asphalt), South of Thomas Road-Ratfliff Road Intersection, North of an E-W running stream

THEORY OF LOCATION: Describe the theory of location for acceptance of this monument with reference to the recording information for the survey upon which this record is derived. Said recorded survey shall be certified by the same professional surveyor who certifies this document, shall identify and accept this monument, and shall have been recorded within (3) years of Form submittal.
Ties prepared by Monroe County Surveyor Kevin P. Enright dated May 25th, 2000 show a "PK nail" was found at this corner. Recovered corner witnesses were checked to confirm the location of the found mag nail was in harmony with the location of the "PI nail" referenced in 2000. The location of the found mag nail was commonly accepted by surveys in the area and its location was accepted and held as said corner.


MONUMENT PRESERVATION: Describe work done to preserve existing monument. Stone mounds should be placed around monuments when stones are readily available. Paint corner stones but not the scribing. A Monroe County "PROTECT NEARBY SURVEY MARKER" sign shall be attached to a steel post when practicable. Note location and relation of corner to sign.
A Monroe County "PROTECT NEARBY SURVEY MARKER" sign was found on the Northeast side of a 9" Dia. Power Pole Southeast of the corner.

GEODETIC COORDINATES: Northing: **1445620.0**, Easting: **3081075.9**


BASIS OF GEODETIC COORDINATES: Describe equipment, date, and personnel used to collect coordinates, datum, epoch, geoid and zone.
Coordinates shown hereon were obtained from GPS observations utilizing the Indiana Real-Time Network (INCORS). Indiana West Zone, NAD83(2011) Epoch 2010.0000, State Plane Grid Coordinates, US Survey Feet. Geoid model G2012BU7. Datum NAD83_NO_TRANS by Jackson Rogers and Eric Deckard on November 8th, 2021.

WITNESS MONUMENT TIES: Describe at least three new BT's and/or witness objects established or work done to preserve existing evidence. The following procedures are provided for guidance. Please utilize professional judgment when choosing witness ties. All ties to BT's should be a magnetic nail and washer (state what kind) set in a hack mark at root crown (less than 12" above ground) perpendicular to center of tree unless otherwise noted. All monuments should be tied to at least three accessories with a minimum of 60° of separation. BTs should be healthy with a minimum DBH of 4". BT description should include tree species, diameter at 4.5' above ground, distance of nail above ground, and description of nail location (e.g., SE side of root). Note bearing from monument to the center of the BT, distance to the nail. Other survey monuments that were located in the vicinity and their relation to the monument may also be included.

ID	Bearing	Distance	Description
B	S 84° E	25.00'	5/8" Dia. Rebar with "Mundy" cap
C	S 17° E	76.80'	Cut "X" in Fire Hydrant Bolt
D	S 18° W	46.50'	Mag nail 9" A.G. in East side of Power Pole



MONUMENT RECORD
Corner ID: **Rich_M11**
Section Corner
Sections 15 & 16- T09N-R02W, 2nd P.M.
Richland Township, Monroe County, Indiana



MONUMENT LOCATION SKETCH: Optional: Attach a sketch or aerial image. Monument sketch is not required for reimbursement.

PHOTO IDENTIFIED: Photograph close up photo of monument and a vicinity photo of the monument that includes the Monroe County “PROTECT NEARBY SURVEY MARKER” sign. Provide photo orientation and date. Additional photos may be included by clicking the “+” button at the end of the horizontal line.
Photo Date: **November 2021**



Photo Orientation & Description: **Looking West at M-11**



Photo Orientation & Description: **Looking South at M-11**

FIELD PERSONNEL:

Field Date: **11/8/21** By: **J.R. & E.D.** Project #: **21-157** Field Book: , page: Notes:

CERTIFICATION:

Professional Surveyor Name: **Eric L. Deckard**
Indiana Professional Surveyor No.: **29900012**
Firm Name: **Deckard Land Surveying**
Date: **12/03/21**


Signature:




Seal:

OFFICE USE ONLY



NOTICE TO PROCEED AND MONUMENT RECORD FORM ISSUED TO:			
Offeror Name: Eric L. Deckard		Firm Name: Deckard Land Surveying, LLC	
Phone: (812)961-0235		Email: Ericdeckard1@msn.com	
Corner Classification: Section Corner		Corner Coordinate Status: Perpetuated	





MONUMENT RECORD
Corner ID: **Rich_M11**
Section Corner
Sections 15 & 16- T09N-R02W, 2nd P.M.
Richland Township, Monroe County, Indiana



Issue Date: 7/12/22	Form Due Date: 7/21/22	Form Receipt Date: 7/21/2022
---------------------	------------------------	------------------------------

COUNTY SURVEYOR APPROVAL: <input checked="" type="checkbox"/> Yes, Signature:  <input type="checkbox"/> No, reasons for denial	Date: 7/19/22	Seal: 
---	---------------	--

SURVEYOR REVIEW BOARD APPROVAL: <input checked="" type="checkbox"/> Yes, Signature:  <input type="checkbox"/> No, reasons for denial	Date: 7/19/22	Seal: 
--	---------------	---